



**Qin Huangdao Huashenglong Electrical Equipment Co.,Ltd.**

Tel :0086-335-8560000

Fax:0086-335-8515333

Mobile(WhatsApp) :0086-13483376954

Skype:happyeveryday934

Email: [hslecsales@aliyun.com](mailto:hslecsales@aliyun.com)

Web: [www.reactorinchina.com](http://www.reactorinchina.com) [www.hslec.com](http://www.hslec.com)

**S(B)H15-M Sealed type Amorphous Alloy Power Transformer**

Basic Order Data need customer to provide:

1. Rated HV and LV
2. Rated Capacity
3. Joint Group: Yyn0 or Dyn11
4. Using condition



Technical Data for your reference

Model	Rated Capacity	Vector Group	Voltage Combination kV		No-load Current	No-load Loss	Load Loss	Short-circuit Impedance	
			High Voltage	Low Voltage					
	Kva		H.V.	L.V.	%	W	(75°C) W	%	
SH15-M-80	80	Dyn11	6 ±5%	6.3	0.4	1.5	75	1530	4.0
SH15-M-100	100					1.4	85	1825	4.0
SH15-M-125	125					1.4	100	2165	4.0
SH15-M-160	160					1.3	115	2635	4.0
SH15-M-200	200					1.3	140	3060	4.0
SH15-M-250	250					1.2	170	3485	4.5
SH15-M-315	315					1.1	205	4165	4.5
SH15-M-400	400					1.1	245	5100	4.0
SH15-M-500	500					1	290	6080	4.0



**Qin Huangdao Huashenglong Electrical Equipment Co.,Ltd.**

Tel :0086-335-8560000

Fax:0086-335-8515333

Mobile(WhatsApp) :0086-13483376954

Skype:happyeveryday934

Email: [hslecsales@aliyun.com](mailto:hslecsales@aliyun.com)

Web: [www.reactorinchina.com](http://www.reactorinchina.com) [www.hslec.com](http://www.hslec.com)

SH15-M-630	630				0.9	345	7225	4.5
SH15-M-800	800				0.9	420	8840	4.5
SH15-M-1000	1000				0.8	495	10370	4.5
SH15-M-1250	1250				0.8	585	12325	4.5
SH15-M-1600	1600				0.7	705	14705	4.5

Note: Data included in the table are for reference only. For more information please contact us.